



ELEMENT	DESCRIPTION	NORM	UNIT	VALUE
PRODUCT	Type			Monomeric PVC film
	Thickness		micron	140 ± 10
	Front colour			White
	Back			Black full coated
	Shrinkage		%	≤ 0.6
	Surface tension		dyne/cm	≥ 30 dyne / cm
	Holes No.		sq inch (mm 25,4x25,4)	Average 130
	Hole Diameter		mm	1.6
	Distance Between Holes		mm	left right 1.25 - Up-Down 2.0
	Hole Space (transparency)		%	40
	Opacity		%	99
	Fire rating	DIN-4102-1		B1
	Available sizes		m	1,06-1,37-1,52*50
ADHESIVE	Type			Clear removable (solvent based pressure sensitive glue)
	Thickness		micron	25 ± 3 micron
	Applications conditions		°C	15°C~33°C (thermal range), ≥8°C min. application temperature. If the glass you mount on is exceeding 44°C, initial tack effects are undone and the film can fall off the glass.
	Initial Adhesion (Ball Tack)	GB4852-84/CNS		≥5 Steel Ball
	Peeling force	FTM 1	N/25 mm	(24 hours) 5 ≤ x ≤ 10
	Expected lifetime			8 months. Six months for a clean removal. Adhesion may increase with time.
	Removable durability			Max one year cleanly removable at the temperature of 18-25°C and RH of 50-60% (provided that the glass surface is very clean when sticking).
LINER	Type			PE coated kraft paper
	Colour			White
	Weight		g/m <sup>2</sup>	140 ± 5
	Release force	FTM 3	N/25 mm	0.05 ≤ x ≤ 0.25

APPLICATIONS	Outdoor digital printing and screen printing one way vision media for signage display, shop window advertising, vehicle graphic, subway and building glass walls.
PRINTABILITY	Media is suitable for all eco-solvent digital printers with cold or heating system applications. All tests are made with the original printer manufacturers inks.
STORAGE PERIOD	12 months under ordinary condition at the average temperature of 22°C and relative humidity of 50-55%.
SAFETY NORMS	Complying with the Italian Decree-Law n. 133 issued on 14.09.2009 and published on the Italian Gazzetta Ufficiale, we inform that the product is compliant with the REACH regulation with regard to the substances and chemicals used in their construction during manufacture. For further information, please refer to the certified copy available of the analyses worked out on the substances taken into consideration by REACH (Registration Evaluation Authorization of Chemicals). <b>RoHS - Cadmium free</b>
NOTES	<i>Published information is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of the products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to changes without prior notice.</i>