Total Eraze White | 50.100N

Total Eraze White is an easy-to-apply whiteboard film, perfect for surfaces like painted walls. Its low-energy lacquer coating ensures effortless ink removal. For optimal results, use our 97.011 Eraze Marker Black or consult the Total Eraze marker compatibility list.

FACE FILM

Polymeric PVC, gloss white

Thickness (µm)	160
Opacity	High

ADHESIVE

Grey-tinted water-based acrylic, high tack permanent

Thickness (µm)	20	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	15	
24 hours (180°) N/25mm	21	

RELEASE LINER

Lay-flat kraft paper liner, one-sided PE-coated

Weight (gsm)	120

PRODUCT APPLICATION

Application method	Dry
Dimensional stability (.mm)	0,3
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70

DURABILITY

Shelf life (months)	24
Outdoor durability (years)	N/A

ROLL SIZES

1370mm x 50m

PRINTING METHOD

UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.